



**CD3**  
**Video Security**

www.eyespyvideo.com  
 24 Hour Sales: 800-568-6871  
 Customer Service: 800-568-9291 (9am - 5pm Central US)  
 Fax: 800-568-6356  
 info@eyespyvideo.com

## PW-24D16 Information



The **PW-24D16** delivers a full 8 amperes of AC electrical current, enough to safely handle up to 16 24v AC CCTV cameras. The PW-24D16 has sixteen power outputs for connecting multiple devices, and each of these voltage outputs provides 24 volts AC voltage with 12 vA maximum current.

Voltage input is 110v AC, 60 Hz with two (2) 2-prong polarized wall plugs (U.S. standard voltage and plug).

However, this power supply is NOT intended for novice CCTV installation. Connecting the PW-24D16 to a 110v AC power source requires soldering the 2-prong AC input cables directly to the PW-24D16's internal transformers (the included power input cords have stripped and tinned ends). In addition, AC voltage outputs for each camera connection consist of bare lead power terminals. In order to connect CCTV cameras or other 24v AC devices to this power supply, a bare power cord from each device must be secured to the output terminals using a screw driver. Installers of this product MUST be sure to follow all instructions and carefully connect all devices.

The PW-24D16 is an economical solution to powering an entire 24v AC CCTV camera surveillance system with a single power supply box.

## PW-24D16 Technical Specifications

Input Voltage	110v AC, 60 Hz
Output Voltage	24 volts AC
Current Delivery	up to 12 vA (volt-amperes) per camera x 16 cameras
Input Voltage	2 x polarized 2-prong standard U.S. 110v AC wall outlet plug
Output Voltage	bare lead wire terminals for hardwire connection
Cord Length	2 x 6' / 1.8 meters
Dimensions	9.7" x 8.3" x 3.4" / 247mm x 210mm x 87mm
Weight	10 lbs., 11 oz. / 4.8 kg
Warranty	one year
*Additional Features	3.5 amp fuse per camera plus two 5 amps main fuses, great for stationary home or office use of multiple Eyespyvideo.com cameras and many other 24v AC devices