



CD3
Video Security

www.eyespyvideo.com
 24 Hour Sales: 800-568-6871
 Customer Service: 800-568-9291 (9am - 5pm Central US)
 Fax: 800-568-6356
 info@eyespyvideo.com

PWR-24D4 Information



The **PWR-24D4** delivers a full 160 volt-amperes of AC electrical current, enough to safely handle up to 4 24v AC CCTV cameras. The PWR-24D4 has four power outputs for connecting multiple devices, and each of these voltage outputs provides 24 volts AC voltage with 40 vA maximum current.

Voltage input is 110v AC, 60 Hz with one 2-prong polarized wall plug (U.S. standard voltage and plug).

However, this power supply is NOT intended for novice CCTV installation. Connecting the PWR-24D4 to a 110v AC power source requires soldering a 2-prong AC input cable directly to the PWR-24D4's internal transformer (the included power input cord has stripped and tinned ends). In addition, AC voltage outputs for each camera connection consist of bare lead power terminals. In order to connect CCTV cameras or other 24v AC devices to this power supply, a bare power cord from each device must be secured to the output terminals using a screw driver. Installers of this product MUST be sure to follow all instructions and carefully connect all devices.

The PWR-24D4 is an economical solution to powering an entire 4-camera 24v AC CCTV surveillance system with a single power supply box.

PWR-24D4 Technical Specifications

Input Voltage	110v AC, 60 Hz
Output Voltage	24 volts AC
Current Delivery	up to 40 vA (volt-amperes) per camera x 4 cameras
Input Plug	polarized 2-prong standard U.S. 110v AC wall outlet plug
Output Plug	bare lead wire terminals for hardwire connection
Cord Length	6' / 1.8 meters
Dimensions	9.7" x 8.3" x 3.4" / 247mm x 210mm x 87mm
Weight	7 lbs., 5 oz. / 3.3 kg
Warranty	one year
*Additional Features	3.5 amp fuse per camera plus 5 amps main fuse, great for stationary home or office use of multiple Eyespyvideo.com cameras and many other 24v AC devices